ACCESSORY

STAINLESS STEEL GOOSENECK ELECTRICAL FLASHING



PRODUCT INFORMATION

Features

- H.D. spun aluminum base with 4" deck flange, 11.5" total flashing base diameter.
- Premium 304 grade 30° stainless steel gooseneck pre-drilled and riveted to spun aluminum base.
- Stainless steel walls 1 mm thickness and 50 mm O.D.
- ¾" thick insulated walls in aluminum base.
- 1.75" I.D. between insulated walls.
- Gooseneck design provides a weatherproof flashing for extending wiring conduit on low slope roof systems.
- Provides electrical access wherever needed on roof.
- ¾" thick polyurethane foam insulated walls.
- Ideal for satellite cable penetrations.

Millenium Quality

Millenium Stainless Steel Gooseneck Electrical Flashings are manufactured under rigorous quality control processes to deliver long-lasting performance, outstanding corrosion resistance, and reliable installation. Every product is engineered to meet the requirements of architects, engineers, and building professionals.

Customer Testimonial

“At last a quality maintenance-free product at an affordable price. Kiss the pitch pans good-bye.”

Darrel Henderson — Superteck Consultants

Millenium Warranty

Millenium provides a limited ten (10) year warranty on materials against manufacturing defects and a one (1) year warranty on the paint finish, where applicable. This warranty does not cover damage resulting from misuse, product modification, or installation that does not comply with Millenium's installation recommendations.

Stainless Steel Gooseneck Electrical Flashing

